

DESKTOP BARCODE
LABEL PRINTER

LK-B12

- Thermal transfer and direct thermal printing
- 127mm/sec speedy label printing
- USB on Board
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Resin, Wax/Resin)
- Paper width adjustable from 18mm to 118mm



INTERFACE



◀ **LK-B12 INTERFACE**
 Standard interface card
 - USB
 Optional interface card
 - Parallel(IEEE-1284)

● **SPECIFICATION**

| ITEM | TYPE | |
|---------------------------|---|------------------------------------|
| MODEL | LK-B12 | |
| PRINT METHOD | Thermal Transfer and Direct Thermal | |
| PRINTING SPEED | 127 mm/sec | |
| PRINT WIDTH | 104mm(4.1") | |
| PRINT LENGTH | 630mm(24.8") | |
| RESOLUTION | 203 DPI(8 dots/mm) | |
| PAPER WIDTH (min~max) | 18mm ~ 118mm(0.7" ~ 4.25") | |
| PAPER ROLL SIZE (min~max) | Internal | Ø 25.4(1")~ Ø 127mm(5.0") |
| | External | Ø 38.1(1.5")~ Ø 200mm(7.8") |
| PAPER THICKNESS | 0.08 ~ 0.18mm | |
| PAPER TYPE | Label, Tag, Continuous, Fanfold | |
| PAPER SENSOR | Label Gap Sensor, Black Mark Sensor, Notch Sensor | |
| RIBBON WIDTH | 33mm ~110mm(1.3 ~ 4.3") | |
| RIBBON LENGTH | 360M, Ø 67mm(2.5") | |
| MEMORY | STANDTAD | 8MB SDRAM, 3MB Flash |
| | OPTION | 4MB Flash |
| BARCODE | 1D | UCC/EAN-128 |
| | 2D | MaxiCode, PDF 417, QR CODE(EPL II) |
| FONT SPECIFICATION | 6 bitmapped - 8x12, 10x16, 12x20, 14x24, 32x48,24x24(KSC5601) | |
| PROGRAMMING LANGUAGE | EPL II Command compatible | |
| POWER | AC 100~240V, 24VDC, 2.5A | |
| DIMENSIONS | 215mm x 287mm x 231mm | |
| WEIGHT(kg) | 3.6kg | |

